

Minimum Pitches for Concrete & Clay Tiles

Tile Material	Profile Type	With Underlay (Refer Note	Without Underlay
Concrete Tiles	Type I*	15°	20°
	Type II	20°	-
	Type III**	20°	-
Clay Tiles	Type I	20°	25°
	Type II	20°	-
	Type III	25°	-
* Monier Hacienda & Villa profile concrete roof tiles conform to the "Type 1" profile type.			
** Monier Horizon, Georgian, Madison profile concrete roof tiles conform to the "Type 3" profile type.			
Type I	Type 1: Double tiles having two distinct watercourses with a minimum watercourse depth of 18mm.		
Type II	Single profile tiles having one watercourse a minimum of 25mm in height		
Type III	Tiles not fitting the Type I or Type II categories, and includes flat tiles and those resembling slated, shakes and shingles.		

b27 monier minimum pitch table.dwg

Monier Roofing
PO Box 188,
Takanini,
Auckland 2245

Technical Help
0800 851 588

Monier Tile Detail: B27

Minimum Pitch Table

planstomonier@csr.co.nz
www.monier.co.nz

Issue 1
27 March 2015
Scale 1:5

Disclaimer: This information is intended solely as a guide for use of Monier products. Before using Monier products you should ensure that the product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose - appropriate expert advice should always be obtained. Monier makes no warranty regarding the use of this information with non-Monier products. © 2014. The copyright of this document is the property of CSR Building Products (NZ) Ltd trading as Monier and shall not be reproduced, copied, loaned or disposed of directly, or indirectly, nor used for any purpose other than that for which it is specifically furnished without prior consent.